


3-WIRES



7382-19



application



- Used with standard outside micrometers to measure pitch diameter of screw threads
- Diameter accuracy: $\pm 0.5\mu\text{m}$
- Cylindricity: $1\mu\text{m}$
- Hardness: HRC60
- Supplied with manufacturer inspection certificate

For outside micrometers with spindle $\text{\O}6.35\text{mm}$ ($\text{\O}D$)

Code	Pin gage diameter	Applicable pitch
7382-11	$\text{\O}0.170\text{mm}$	0.2mm, 0.25mm, 0.3mm
7382-12	$\text{\O}0.195\text{mm}$	0.35mm
7382-13	$\text{\O}0.220\text{mm}$	0.4mm
7382-14	$\text{\O}0.250\text{mm}$	0.45mm
7382-15	$\text{\O}0.290\text{mm}$	0.5mm
7382-16	$\text{\O}0.335\text{mm}$	0.6mm
7382-17	$\text{\O}0.390\text{mm}$	0.7mm
7382-18	$\text{\O}0.455\text{mm}$	0.75mm, 0.8mm
7382-19	$\text{\O}0.530\text{mm}$	0.9mm
7382-110	$\text{\O}0.620\text{mm}$	1.0mm
7382-111	$\text{\O}0.725\text{mm}$	1.25mm
7382-112	$\text{\O}0.895\text{mm}$	1.5mm
7382-113	$\text{\O}1.100\text{mm}$	1.75mm, 2.0mm
7382-114	$\text{\O}1.350\text{mm}$	2.5mm
7382-115	$\text{\O}1.650\text{mm}$	3.0mm
7382-116	$\text{\O}2.050\text{mm}$	3.5mm
7382-117	$\text{\O}2.550\text{mm}$	4mm, 4.5mm
7382-118	$\text{\O}3.200\text{mm}$	5mm, 5.5mm, 6mm
7382-1S	18 pairs/set, including all above 3-wires	

For outside micrometers with spindle $\text{\O}6.50\text{mm}$ ($\text{\O}D$)

Code	Pin gage diameter	Applicable pitch
7382-21	$\text{\O}0.170\text{mm}$	0.2mm, 0.25mm, 0.3mm
7382-22	$\text{\O}0.195\text{mm}$	0.35mm
7382-23	$\text{\O}0.220\text{mm}$	0.4mm
7382-24	$\text{\O}0.250\text{mm}$	0.45mm
7382-25	$\text{\O}0.290\text{mm}$	0.5mm
7382-26	$\text{\O}0.335\text{mm}$	0.6mm
7382-27	$\text{\O}0.390\text{mm}$	0.7mm
7382-28	$\text{\O}0.455\text{mm}$	0.75mm, 0.8mm
7382-29	$\text{\O}0.530\text{mm}$	0.9mm
7382-210	$\text{\O}0.620\text{mm}$	1.0mm
7382-211	$\text{\O}0.725\text{mm}$	1.25mm
7382-212	$\text{\O}0.895\text{mm}$	1.5mm
7382-213	$\text{\O}1.100\text{mm}$	1.75mm, 2.0mm
7382-214	$\text{\O}1.350\text{mm}$	2.5mm
7382-215	$\text{\O}1.650\text{mm}$	3.0mm
7382-216	$\text{\O}2.050\text{mm}$	3.5mm
7382-217	$\text{\O}2.550\text{mm}$	4mm, 4.5mm
7382-218	$\text{\O}3.200\text{mm}$	5mm, 5.5mm, 6mm
7382-2S	18 pairs/set, including all above 3-wires	