



- Peak hold and automatic release function
 Set upper and lower limits, red and green indicator and buzzer alarm
 Automatic conversion of three units: N, kgf, lbf
 Built in printer
 Automatic power off



SPECIFICATION

Code	ISF-S10	ISF-S20	ISF-S30	ISF-S50	ISF-S100	ISF-S200
Maximum load	10N	20N	30N	50N	100N	200N
Resolution	0.001N	0.002N	0.01N	0.01N	0.02N	0.05N
Range of digital scale	65mm	65mm	65mm	95mm	95mm	95mm
Resolution of digital scale	0.01mm	0.01mm	0.01mm	0.01mm	0.01mm	0.01mm
Disk diameter	Ø30mm	Ø30mm	Ø30mm	Ø49mm	Ø49mm	Ø49mm
Maximum free length of spring	65mm	65mm	65mm	95mm	95mm	95mm
Measuring range of force	5%~100% (maximum load)					
Accuracy of force	±1% (maximum load)					
Data output	RS232					
Power supply	220V, 50/60Hz					
Dimension	300×235×600mm	300×235×600mm	300×235×600mm	300×235×620mm	300×235×620mm	300×235×620mm
Weight	13.2kg	13.2kg	13.2kg	17.3kg	19.1kg	19.1kg

Code	ISF-S300	ISF-S500	ISF-S1000	ISF-S2000	ISF-S5000	
Maximum load	300N	500N	1000N	2000N	5000N	
Resolution	0.1N	0.1N	0.2N	0.5N	1N	
Range of digital scale	95mm	95mm	150mm	150mm	150mm	
Resolution of digital scale	0.01mm	0.01mm	0.01mm	0.01mm	0.01mm	
Disk diameter	Ø49mm	Ø49mm	Ø108mm	Ø108mm	Ø108mm	
Maximum free length of spring	95mm	95mm	200mm	200mm	200mm	
Measuring range of force	5%~100% (maximum load)					
Accuracy of force	±1% (maximum load)					
Data output	RS232					
Power supply	220V, 50/60Hz					
Dimension	300×235×620mm	300×235×620mm	490×300×920mm	490×300×920mm	490×300×920mm	
Weight	19.1kg	20.8kg	47.5kg	47.5kg	47.5kg	

STANDARD DELIVERY

Main unit	1 pc			